

Datum: 28.05.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



2/2-el.mag.vent.,NO,vod. krm.,24V DC,NBR,G1/2,PN0.2-16bar

Kategorija: [Solenoid valve, NO, pilot-operated](#)
Šifra: **102955RIE**

(slika je simbolična)

Kratek opis

2/2-way solenoid valve brass, NO, pilot operated, 24 V DC,
Medium temperature -10 °C to 90 °C, G 1/2, PN 0.2 - 16 bar
Economy series available in three different versions

- Directly operated
- Combined operation
- Pilot-operated

For all applications with compressed air, neutral gases or
low-viscosity, neutral media.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-10
Min. temperatura medija [°C]	-10
	For connector socket
Električni priključek	Pg 9/Pg 11 acc. to ISO 4400
Ffunkcija	normally open (NO)
IP zaščita	IP 65 (with connector socket fitted)
Navoj	G 1/2
Notranji deli	Stainless steel
Ohišje	Brass
Sedež ventila	Brass
Tesnilo	NBR
Min. obratovalni tlak [bar]	0.2
Vrsta	4
DN	13
Max. obratovalni tlak [bar]	16
A [mm]	54.0
B [mm]	66.0
Max. sobna temperatura [°C]	80
Max. temperatura medija [°C]	90