



2/2-potni el.mag. ventil, NC, direk. upr., 230 V, 50 - 60 Hz

Kategorija: [Solenoid valve, NC, directly operated](#)
Šifra: **102821RIE**

(slika je simbolična)

Kratek opis

2/2-way solenoid valve, brass, NC, direc.
operat., 230V, 50-60Hz, Med. temp. -25 to 80°C, Ambient
temp. -25 to 55°C, NBR, G 1/4, PN 0-12bar
Standard series, proven over many years, available in three
different versions
- Directly operated
- Combined operation
- Pilot-operated
For all applications with compressed air, neutral gases or
low-viscosity, neutral media.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-25
Min. temperatura medija [°C]	-25
Električni priključek	ISO 4400, cable socket (Pg 11P)
Ffunkcija	normally closed (NC)
IP zaščita	IP65 (with connector socket fitted)
Navoj	G 1/4
Notranji deli	Stainless steel
Ohišje	Brass
Sedež ventila	Brass
Standardni navoj	G thread acc. to DIN EN ISO 228-1
Tesnilo	NBR
Vrsta	2
DN	3.2
Max. obratovalni tlak [bar]	12
B [mm]	30.0
Max. sobna temperatura [°C]	55
Max. temperatura medija [°C]	80
A [mm]	91.0