

Datum: 27.05.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



2/2-potni el.mag. ventil, NO, prisil. vod. krm., 24 V DC, 3/8

Kategorija: [Solenoid valve, NO, combined operation](#)
Šifra: **102851RIE**

(slika je simbolična)

Kratek opis

2/2-way solenoid valve brass, NO, force pilot operated, 24 V DC, Rp 3/8, NBR, Medium temp. -20 °C to 85 °C, PN 0 - 9 bar
Standard series, proven over many years, available in three different versions

- Directly operated
- Combined operation
- Pilot-operated

For all applications with compressed air, neutral gases or low-viscosity, neutral media.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Električni priključek	ISO 4400; cable socket (Pg 11P)
Ffunkcija	normally open (NO)
IP zaščita	IP65 (with connector socket fitted)
Navoj	Rp 3/8
Notranji deli	Stainless steel
Ohišje	Brass
Sedež ventila	Brass
Standardni navoj	Rp thread acc. to ISO 7-1
Tesnilo	NBR
Vrsta	3
Max. obratovalni tlak [bar]	9
DN	16
Max. sobna temperatura [°C]	50
B [mm]	70.0
A [mm]	80.0
Max. temperatura medija [°C]	85