



(slika je simbolična)

## cev spojko, PUR, cev Ø 16x11, dolžina 15,0 m

Kategorija: [Straight hose and DN 7.6 standard coupling](#)  
Šifra: **113498RIE**

### Kratek opis

Hose coupling set, PUR, I.D. 7.6, Medium / ambient temperature -20 °C to 60 °C, Hose Ø 16x11, PN max. 16 bar, Length 15 m  
Spiral or straight polyurethane hose, completely assembled with DN 7.6 safety coupling and steel plugs.  
Coupling  
Safety coupling made of steel / nickel-plated brass for high flow rates, specially designed for all applications susceptible to severe mechanical wear.  
Strong, impact and vibration-resistant design for demanding environments.  
Polyurethane hose  
Extremely flexible spiral hose with excellent kink resistance and insensitive to dirt.  
Combines high tear, tensile and impact strength with a long service life and optimal ageing qualities.  
This hose is additionally characterised by outstanding resistance to abrasion and resistance to UV.  
Not suitable for direct attachment to pulsating tools.  
We recommend using our vibration dampers, according to ISO 6150 § 7.1.

### Tehnične Specifikacije

|                              |                    |
|------------------------------|--------------------|
| Min. sobna temperatura [°C]  | -20                |
| Min. temperatura medija [°C] | -20                |
| Material                     | Polyurethane (PUR) |
| Storitev dolžina max. [m]    | 15.0               |
| Max. obratovalni tlak [bar]  | 16                 |
| Velikost cevi [mm]           | 16x11              |
| Max. sobna temperatura [°C]  | 60                 |
| Max. temperatura medija [°C] | 60                 |