



(slika je simbolična)

Filter»FUTURA«Kov. pos.5µm, Vel. 1, G3/8, Pol avto.

Kategorija: [Filter with metal bowl and sight glass](#)
Šifra: **156553RIE**

Kratek opis

Filter »FUTURA« with metal container and viewing tube, 5 µm, Size 1, G 3/8, 1.5 - 16 bar, Temp. -10 °C to 50 °C, Semi-automatic
Filters with excellent flow rates in modern design.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Element filtra	Cellpor (PE)
Merjenje pretoka	At $P_2 = 6$ bar and pressure drop $\Delta p = 1$ bar
Navoj	G 3/8
Odtok kondenzata	Semi-automatic
Ohišje	PA66 GF60
Posoda	Metal container with viewing tube
Priključni navoj	Material: Die-cast zinc
Serijska	FUTURA
Srednje	Compressed air, neutral gases
Tesnilo	NBR
Velikost	1
Min. vhodni tlak [bar]	1.5
Rang filtra [µm]	5
Max. vhodni tlak [bar]	16
C [mm]	34.0
Max. temperaturno območje [°C]	50
A [mm]	52.0
B [mm]	164.0
Pretok [l/min]	2200