

Datum: 23.05.2024

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)

(slika je simbolična)

## Filter reg. »Stinard«PC zbir.40 µm, Vel.4, G 3/4

Kategorija: [Filter regulator with polycarbonate bowl](#)  
Šifra: **174092RIE**

### Kratek opis

Filter regulator »Standard« PC container, press. gauge, 40 µm, Size 4, G 3/4, PE max. 16 bar, Control range 0.5-10 bar, pilot con.  
Reversible diaphragm pressure regulators, independent of inlet pressure, with selfrelieving design, combined with a centrifugal separator.

### Tehnične Specifikacije

|                              |                                                                      |
|------------------------------|----------------------------------------------------------------------|
| Merjenje pretoka             | At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta p = 1$ bar |
| Navoj                        | G 3/4                                                                |
| Odtok kondenzata             | Semi-automatic                                                       |
| Ohišje                       | Aluminium, painted silver                                            |
| Posoda                       | Polycarbonate container                                              |
| Serijska                     | Standard                                                             |
| Tesnilo                      | NBR                                                                  |
| Min. krmilno območje [bar]   | 0.5                                                                  |
| Velikost                     | 4                                                                    |
| Max. krmilno območje [bar]   | 10                                                                   |
| Max. vhodni tlak [bar]       | 16                                                                   |
| Zaslon manometra max. [bar]  | 16                                                                   |
| DN                           | 25                                                                   |
| Rang filtra [µm]             | 40                                                                   |
| Max. sobna temperatura [°C]  | 60                                                                   |
| Max. temperatura medija [°C] | 60                                                                   |
| A [mm]                       | 125.0                                                                |
| C [mm]                       | 129.0                                                                |
| D [mm]                       | 263.0                                                                |
| Pretok [l/min]               | 12000                                                                |