

Datum: 23.05.2024



(slika je simbolična)

## Filter regulator »GA«, PC zbiralnik, 5 µm, Velikost 400, G 1/2

Kategorija: [Filter regulator with PC bowl, bowl guard](#)Šifra: **178474RIE**

### Kratek opis

Filter regulator »GA«, with PC container, Protective cage, Mounting bracket, 5 µm, Size 400, G 1/2, Input pressure max. 10 bar  
Reversible diaphragm pressure regulators, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator. The pressure setting can be locked by pushing the button down.

### Tehnične Specifikacije

|                                |                                                                      |
|--------------------------------|----------------------------------------------------------------------|
| Min. temperaturno območje [°C] | -5                                                                   |
| Merjenje pretoka               | At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta p = 1$ bar |
| Navoj                          | G 1/2                                                                |
| Odtok kondenzata               | Semi-automatic                                                       |
| Ohišje                         | Die-cast aluminium                                                   |
| Posoda                         | Polycarbonate container with protective cage                         |
| Serijska                       | GA                                                                   |
| Tesnilo                        | NBR                                                                  |
| Vzmet pokrova motorja          | POM                                                                  |
| Min. krmilno območje [bar]     | 1.5                                                                  |
| Rang filtra [µm]               | 5                                                                    |
| Max. krmilno območje [bar]     | 9                                                                    |
| Max. vhodni tlak [bar]         | 10                                                                   |
| Max. temperaturno območje [°C] | 70                                                                   |
| A [mm]                         | 80.0                                                                 |
| C [mm]                         | 108.0                                                                |
| D [mm]                         | 177.5                                                                |
| B [mm]                         | 285.5                                                                |
| Velikost                       | 400                                                                  |
| Pretok [l/min]                 | 4000                                                                 |