



(slika je simbolična)

## Filter regulator iz nerjevečega jekla, G 1/4, 0.4 - 4.0 bar

Kategorija: [Stainless steel casting filter regulators 1.4401](#)  
Šifra: **137335RIE**

### Kratek opis

Stainless steel casting filter regulator, 1.4401, with secondary venting (reversible), Size 1, G 1/4, Control range 0.4 - 4.0 bar  
Stainless steel filter regulators with self-relieving (not for liquid media) for use in the chemical industry, mining, plant construction and special machinery industries, pneumatics, etc.  
Pressure setting by T-handle.

### Tehnične Specifikacije

|                              |                                                                            |
|------------------------------|----------------------------------------------------------------------------|
| Membrane                     | NBR/PTFE                                                                   |
| Merjenje pretoka             | At $P_1 = 10$ bar, $P_2 = 6$ bar and pressure drop $\Delta p \Delta 1$ bar |
| Navoj                        | G 1/4                                                                      |
| Odtok kondenzata             | Manual drain valve                                                         |
| Ohišje                       | Stainless steel casting 1.4401 (AISI 316)                                  |
| Tesnilo                      | NBR                                                                        |
| Min. krmilno območje [bar]   | 0.4                                                                        |
| Velikost                     | 1                                                                          |
| Max. krmilno območje [bar]   | 4                                                                          |
| Rang filtra [ $\mu$ m]       | 25                                                                         |
| Max. vhodni tlak [bar]       | 30                                                                         |
| Max. sobna temperatura [°C]  | 60                                                                         |
| A [mm]                       | 62.0                                                                       |
| Max. temperatura medija [°C] | 80                                                                         |
| C [mm]                       | 115.0                                                                      |
| B [mm]                       | 227.0                                                                      |
| Pretok [l/min]               | 2095                                                                       |