

Datum: 26.05.2024



## Filter regulator »multifix-mali«, Kovinska posoda, G 1/8, 0.5-10

Kategorija: [Filter regulator with metal bowl, pressure gauge](#)Šifra: **100355RIE**

(slika je simbolična)

### Kratek opis

Filter regulator »multifix-mini«, Metal container, press. gauge, 5  $\mu$ m, G 1/8, Input pressure max. 16 bar, Control range 0.5-10 bar  
Reversible diaphragm pressure regulators, independent of inlet pressure, with secondary ventilation, in combination with a centrifugal separator. The pressure setting can be locked by pressing in the handwheel.

### Tehnične Specifikacije

|                              |                                                      |
|------------------------------|------------------------------------------------------|
| Merjenje pretoka             | At $P_1 = 10$ bar, $P_2 = 6.3$ bar and pressure drop |
|                              | $\Delta p = 1$ bar                                   |
| Navoj                        | G 1/8                                                |
| Odtok kondenzata             | Semi-automatic                                       |
| Ohišje                       | Die-cast zinc                                        |
| Posoda                       | Metal container                                      |
| Serijska                     | multifix-mini                                        |
| Tesnilo                      | NBR                                                  |
| Vzmet pokrova motorja        | POM-brass                                            |
| Min. krmilno območje [bar]   | 0.5                                                  |
| DN                           | 5                                                    |
| Rang filtra [ $\mu$ m]       | 5                                                    |
| Max. krmilno območje [bar]   | 10                                                   |
| Max. vhodni tlak [bar]       | 16                                                   |
| Zaslon manometra max. [bar]  | 16                                                   |
| A [mm]                       | 40.0                                                 |
| Max. sobna temperatura [°C]  | 60                                                   |
| Max. temperatura medija [°C] | 60                                                   |
| C [mm]                       | 63.0                                                 |
| D [mm]                       | 99.0                                                 |
| B [mm]                       | 162.0                                                |
| Pretok [l/min]               | 1450                                                 |