

Datum: 23.05.2024



(slika je simbolična)

Filter regulator »Stinard-mali«, Kovinska posoda, 5 µm, G 1/8

Kategorija: [Filter regulator with metal bowl](#)Šifra: **100783RIE**

Kratek opis

Filter regulator »Standard-mini« with metal container incl. press. gauge and control cabinet nut, 5 µm, Size 0, G 1/8, 0.5-10 bar
Compact, reversible diaphragm pressure regulators, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator. The pressure setting can be locked by pushing the knob down.

Tehnične Specifikacije

Merjenje pretoka	At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Navoj	G 1/8
Odtok kondenzata	Manual
Ohišje	Die-cast zinc, painted silver
Posoda	Metal container
Serijska	Standard-mini
Tesnilo	NBR
Vzmet pokrova motorja	POM-brass
Min. krmilno območje [bar]	0.5
DN	5
Rang filtra [µm]	5
Max. krmilno območje [bar]	10
Zaslon manometra max. [bar]	16
Max. vhodni tlak [bar]	25
A [mm]	40.0
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
C [mm]	65.0
D [mm]	98.5
B [mm]	163.5
Pretok [l/min]	350