

Datum: 26.05.2024

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)

(slika je simbolična)

## Filter-regulator Zašč. kletka Vel. 1, G 1/2, 0.5 - 16 bar

Kategorija: [Combined service unit, PC bowl and bowl guard](#)  
Šifra: **101103RIE**

### Kratek opis

Combi-service unit with PC container and Protective cage,  
Size 1, G 1/2, Input pressure max. 16 bar, Control range 0.5  
- 16 bar

A filter, pressure regulator and oil-mist lubricator combined  
in a single device with an extremely compact design.

The pressure setting can be locked by pushing the knob  
down.

Oil can be filled under pressure.

### Tehnične Specifikacije

|                                 |                                                                            |
|---------------------------------|----------------------------------------------------------------------------|
| Merjenje pretoka                | At $P_1 = 8$ bar, $P_2 = 6$ bar<br>and pressure drop $\Delta p =$<br>1 bar |
| Navoj                           | G 1/2                                                                      |
| Odtok kondenzata                | Manual drain valve                                                         |
| Ohišje                          | Die-cast zinc<br>Polycarbonate                                             |
| Posoda                          | container with<br>protective cage                                          |
| Tesnilo                         | NBR                                                                        |
| Vidna kupola                    | PA                                                                         |
| Vzmet pokrova motorja           | PA                                                                         |
| Min. krmilno območje [bar]      | 0.5                                                                        |
| Velikost                        | 1                                                                          |
| Max. krmilno območje<br>[bar]   | 16                                                                         |
| Max. vhodni tlak [bar]          | 16                                                                         |
| Rang filtra [ $\mu$ m]          | 40                                                                         |
| Max. sobna temperatura<br>[°C]  | 50                                                                         |
| Max. temperatura medija<br>[°C] | 50                                                                         |
| A [mm]                          | 65.0                                                                       |
| C [mm]                          | 68.5                                                                       |
| B [mm]                          | 217.0                                                                      |
| Pretok [l/min]                  | 1000                                                                       |