



(slika je simbolična)

## Filter z aktivnim ogljem z diferencialnim manometrom, G 1/2

Kategorija: [Activated carbon filter with diff. pressure gauge](#)Šifra: **101578RIE**

### Kratek opis

Active charcoal filter with differential pressure gauge, 0.005 mg/m<sup>3</sup>, G 1/2, Input pressure 4 - 16 bar, Temp. 5 °C to 60 °C For adsorbing vaporous media.  
A micro-filter must be connected upstream if dried air is not available.

### Tehnične Specifikacije

|                                                      |                                                       |
|------------------------------------------------------|-------------------------------------------------------|
| Element filtra                                       | Activated carbon                                      |
| Merjenje pretoka                                     | At P <sub>1</sub> = 6 bar and pressure drop Δp = 0.5% |
| Navoj                                                | G 1/2                                                 |
| Ohišje                                               | Aluminium                                             |
| Posoda filtra                                        | Aluminium                                             |
| Vsebnost olja v ostanku [mg/m <sup>3</sup> ]         | 0.005                                                 |
| Max. označeni razpon diferencialnega manometra [bar] | 2                                                     |
| Min. vhodni tlak [bar]                               | 4                                                     |
| Min. sobna temperatura [°C]                          | 5                                                     |
| Min. temperatura medija [°C]                         | 5                                                     |
| Max. vhodni tlak [bar]                               | 16                                                    |
| C [mm]                                               | 57.0                                                  |
| Max. sobna temperatura [°C]                          | 60                                                    |
| Max. temperatura medija [°C]                         | 60                                                    |
| A [mm]                                               | 83.0                                                  |
| B2 [mm]                                              | 245.0                                                 |
| D [mm]                                               | 263.0                                                 |
| B1 [mm]                                              | 344.0                                                 |
| Pretok [l/min]                                       | 500                                                   |