

Datum: 28.05.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



(slika je simbolična)

Hitre spojke I.D. 10, Težka obilka, R 3/8 zunanji navoj

Kategorija: [Quick disconnect coupling DN 10, male](#)
Šifra: **107465RIE**

Kratek opis

Quick-connect coupling I.D. 10, galvanised steel / brass, Robust design, R 3/8 ET, Operating pressure max. 16 bar One-hand quick disconnect couplings, one side sealing, that combine optimal flow rates (approx. 4 times as high as the popular standard coupling DN 7.2) with minimal coupling forces.

Suitable for all applications with an above-average air requirement and characterised by extreme conditions!

Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Material	Nickel-plated steel, nickel-plated brass
Merjenje pretoka	at 6 bar and $\Delta p = 0.5$ bar
Povezava	R 3/8 ET
Tesnilo	NBR
DN	10
Max. obratovalni tlak [bar]	16
a/f [mm]	24
Dolžina [mm]	68.3
Max. temperaturno območje [°C]	100
Pretok	3900 l/min (air)