

Datum: 28.05.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



(slika je simbolična)

Hitre spojke I.D. 5, zunanji navoj medenina, cev I.D. 5

Kategorija: [Quick disconnect coupling DN 5, with hose stem](#)
Šifra: **107132RIE**

Kratek opis

Quick-connect coupling I.D. 5, bright brass, Sleeve I.D. 5,
Operating pressure 0 - 35 bar, Medium / ambient temp. -20
°C to 100 °C

"

One-hand quick disconnect couplings, one side sealing,
compact with a large bore and only a small pressure drop.
To prevent injuries or a "whiplash" effect, we recommend
that the plug-in nipple is held with one hand during
uncoupling.

Areas of application: Pneumatic system, measurement,
monitoring and control systems, manufacturing industry,
medical technology, chemical / pharmaceutical industry,
automotive, food technology.

"

Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Delovni tlak	0 to 35 bar, maximum static working pressure (non-pulsating)
Krogla	Stainless steel
Merjenje pretoka	at 6 bar and $\Delta p = 0.5$ bar
Ohišje	Brass with a bare metal surface
Povezava	I.D. 5
Pritrdilni obroč	Stainless steel
Rokav	Brass with a bare metal surface
Telo ventila	Brass with a bare metal surface
Tesnilo	NBR
Vzmet	Stainless steel
DN	5
Dolžina [mm]	46.0
Max. sobna temperatura [°C]	100
Max. temperatura medija [°C]	100
Pretok	560 l/min (air)