



## Hitre spojke I.D. 7.2Z.N. Med.G 1/4 Z.N.

Kategorija: [Quick disconnect coupling DN 7.2, male](#)  
Šifra: **107208RIE**

(slika je simbolična)

### Kratek opis

Quick-connect coupling I.D. 7.2, bright brass, G 1/4 ET,  
Operating pressure 0 - 35 bar, Med./ambient temp. -20 °C to  
100 °C

"

Universal, one-hand quick disconnect couplings, one side  
sealing, suitable for a wide range of tasks and applications!  
The closed sleeve protects the coupling from dirt.

To prevent injuries or a "whiplash" effect, we recommend  
that the plug-in nipple is held with one hand during  
uncoupling.

These quick disconnect couplings are not suitable for direct  
attachment to pulsating tools.

We recommend using our vibration dampers, according to  
ISO 6150 § 7.1.

Areas of application: Pneumatic system, machine and plant  
engineering, measurement, monitoring and control systems,  
manufacturing industry, medical technology, chemical /  
pharmaceutical industry, workshops, automotive.

"

### Tehnične Specifikacije

|                                 |                                                                    |
|---------------------------------|--------------------------------------------------------------------|
| Min. sobna<br>temperatura [°C]  | -20                                                                |
| Min. temperatura<br>medija [°C] | -20                                                                |
| Delovni tlak                    | 0 to 35 bar, maximum<br>static working pressure<br>(non-pulsating) |
| Merjenje pretoka                | at 6 bar and $\Delta p = 0.5$ bar                                  |
| Ohišje                          | Brass with a bare metal<br>surface                                 |
| Povezava                        | G 1/4 ET                                                           |
| Pritrdilni obroč                | Stainless steel                                                    |
| Rokav                           | Brass with a bare metal<br>surface                                 |
| Telo ventila                    | Brass with a bare metal<br>surface                                 |
| Tesnilo                         | NBR                                                                |
| Vzmet                           | Stainless steel                                                    |
| Zaporni zatič                   | Stainless steel                                                    |
| DN                              | 7.2                                                                |
| a/f [mm]                        | 22                                                                 |
| Dolžina [mm]                    | 40.0                                                               |
| Max. sobna<br>temperatura [°C]  | 100                                                                |
| Max. temperatura<br>medija [°C] | 100                                                                |
| Pretok                          | 1000 l/min (air)                                                   |