

Datum: 27.05.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si

(slika je simbolična)

Hitre spojke I.D. 7.8visok pretokG 1/4 N.N.

Kategorija: [Quick disconnect coupling DN 7.8, female](#)
Šifra: **107409RIE**

Kratek opis

Quick-connect coupling I.D. 7.8, High flow rate, G 1/4 IT,
Operating pressure 0 - 35 bar, Medium / ambient temp. -20
°C to 40 °C

"

One-hand quick disconnect couplings, one side sealing, that
combine high flow rates (approx. twice as high as the
popular DN 7.2 standard coupling) with minimal coupling
forces.

Suitable for all applications with an above-average air
requirement!

To prevent injuries or a "whiplash" effect, we recommend
that the plug-in nipple is held with one hand during
uncoupling.

These quick disconnect couplings are not suitable for direct
attachment to pulsating tools.

We recommend using our vibration dampers, according to
ISO 6150 § 7.1.

Areas of application: Pneumatic system, machine and plant
engineering, measurement, monitoring and control systems,
manufacturing industry, medical technology, chemical /
pharmaceutical industry, workshops, automotive, food
technology, aerospace.

"

Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Krogla	Stainless steel
Merjenje pretoka	at 6 bar and $\Delta p = 0.5$ bar
Navojni kos	Nickel-plated brass
Povezava	G 1/4 IT
Pritrdilni obroč	Stainless steel
Sedež ventila	Brass
Sprostitveni rokav	Extremely robust, ergonomic plastic
Telo ventila	Steel, QPQ treated
Tesnilo	NBR
Ventil	Brass
Vzmet	Stainless steel
DN	7.8
a/f [mm]	19
Max. obratovalni tlak [bar]	35
Max. sobna temperatura [°C]	40
Max. temperatura medija [°C]	40
Dolžina [mm]	59.0
Pretok	2100 l/min (air)