

Datum: 26.05.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



(slika je simbolična)

Hitre spojke z N.N. I.D. 2.7iz med.M5 N.N.

Kategorija: [Quick disconnect coupling DN 2.7, female](#)
Šifra: **107071RIE**

Kratek opis

Quick-connect coupling I.D. 2.7, bright brass, M5 IT,
Operating pressure 0 - 35 bar, Medium / ambient temp. -20
°C to 100 °C

"

One-hand quick disconnect couplings, one side sealing,
extremely compact with a large bore and only a small
pressure drop.

To prevent injuries or a ""whiplash"" effect, we recommend
that the plug-in nipple is held with one hand during
uncoupling.

Areas of application: Pneumatic system, machine and plant
engineering, measurement, monitoring and control systems,
manufacturing industry, medical technology, chemical /
pharmaceutical industry, automotive.

"

Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Delovni tlak	0 to 35 bar, maximum static working pressure (non-pulsating)
Krogla	Stainless steel
Merjenje pretoka	at 6 bar and $\Delta p = 0.5$ bar
Ohišje	Brass with a bare metal surface
Povezava	M5 IT
Pritrdilni obroč	Stainless steel
Rokav	Brass with a bare metal surface
Telo ventila	Brass with a bare metal surface
Tesnilo	NBR
Vzmet	Stainless steel
DN	2.7
a/f [mm]	9
Dolžina [mm]	25.0
Max. sobna temperatura [°C]	100
Max. temperatura medija [°C]	100
Pretok	165 l/min (air)