


Datum: 27.05.2024

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)



(slika je simbolična)

## Kaljeni cevni vtikač DN 9, zunanji navoj, M14x1.5, dolžina 15

Kategorija: [Push-in plug DN 9, without shut-off valve, ET](#)  
Šifra: **107975RIE**

### Kratek opis

Tempered plug-in nipple DN 9, Exterior thread, Brass 2.0401, M14x1.5, Operating pressure max. 15 bar, Temp. -20 °C to 160 °C  
Compatible with HASCO Z 8 system.  
For temperature control applications involving hot or cold water or heat transfer oil.  
Optionally with free passage, one or both sides sealing.  
Female-threaded couplings and plugs with female-threaded PTFE seal.

### Tehnične Specifikacije

|                              |                         |
|------------------------------|-------------------------|
| Min. sobna temperatura [°C]  | -20                     |
| Min. temperatura medija [°C] | -20                     |
| Krogla                       | Stainless steel         |
| Material                     | Brass 2.0401            |
| Navoj                        | M14x1.5                 |
| Pritrdilni obroč             | Stainless steel         |
| Srednje                      | Air, water, oil, vacuum |
| Tesnilo                      | FPM (PTFE coated)       |
| Vzmet                        | Stainless steel         |
| a/f [mm]                     | 15                      |
| Max. obratovalni tlak [bar]  | 15                      |
| Dolžina [mm]                 | 26.0                    |
| Max. sobna temperatura [°C]  | 160                     |
| Max. temperatura medija [°C] | 160                     |