

Datum: 27.05.2024

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)



(slika je simbolična)

## Kamlok hitra spojka,thread, A tip, 1.4401, G 1

Kategorija: [Kamlok male adapter, female threaded, Part A](#)  
Šifra: **108140RIE**

### Kratek opis

Kamlok quick-connect plug with interior thread, A type, Stainless steel 1.4401, G 1, Plug Ø 37 mm, Pressure max. 16 bar

High-quality, robust, universal coupling system with a safety clamp for quick and easy connection of two hoses or for joining one hose to a machine connection.

A male part and a female part are joined together by shifting the handles.

There is no need to turn the hose!

Kamlok stainless steel couplings are designed for use with corrosive media in the chemical and petrochemical industries, steelmaking, shipbuilding, agriculture, etc.

### Tehnične Specifikacije

|                                |                                    |
|--------------------------------|------------------------------------|
| Min. temperaturno območje [°C] | -20                                |
| Navoj                          | G 1                                |
| Tesnilo                        | NBR, resistant to oils and benzine |
| Max. obratovalni tlak [bar]    | 16                                 |
| Vtič Ø [mm]                    | 37                                 |
| L [mm]                         | 44.7                               |
| Max. temperaturno območje [°C] | 95                                 |