

Datum: 27.05.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



(slika je simbolična)

Kot. varnos. ventil, za tekoč., G 2, vkl. prit. 2.5 bar

Kategorija: [Angle-tip Varnostni ventil G 2](#)
Šifra: **105640RIE**

Kratek opis

Corner safety valve, for liquids, Red brass, NBR, Operating temp. -10 °C to 110 °C, G 2, AF 70, Trigger pressure 2.5 bar
For non-toxic, non-flammable liquids.
No evaporation allowed when blowing off.
With diaphragm to protect the spring and with lifting device.
Type-tested, TÜV-SV. 749. F

Tehnične Specifikacije

Min. delovna temperatura [°C]	-10
Membrane	NBR
Navoj	G 2
Notranji deli	Brass
Ohišje	Bronze
	Each with female thread type G acc. to DIN EN ISO 228-1
Vstop in izstop	C steel
Vzmet	Brass
Vzmet pokrova motorja	Brass
Min. prilagoditveno območje [bar]	1
Min. nastavljeni tlak [bar]	2.5
Max. območje nastavitve [bar]	10
L2 [mm]	48.0
L1 [mm]	56.0
a/f [mm]	70
Max. delovna temperatura [°C]	110
H [mm]	200.0