

Datum: 26.05.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



Krogelni ventil 3/2 »FUTURA«, zaklepni, Velikost 2, G 1/2

Kategorija: [Ball valves](#)
Šifra: **100286RIE**

(slika je simbolična)

Kratek opis

Ball valve 3/2-way »FUTURA«, lockable, Size 2, G 1/2,
Exhaust G 1/2, Input pressure max. 16 bar, Temperature -10 °C to 50 °C
Lockable ball valve, 3/2-way type including silencer, mechanically operated.
Rotary switch can be turned 90°, with indication of positions:
Horizontal: Input closed - outlet exhausted
Vertical: Flow open - exhaust closed
Exhaust air can be collected.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Izpušni zrak	G 1/2 At $P_2 = 6$ bar and pressure drop $\Delta p = 1$ bar
Merjenje pretoka	G 1/2 PA66 GF60
Navoj	Material: Die-cast zinc
Ohišje	FUTURA
Priključni navoj	Compressed air, neutral gases
Serijska	2
Srednje	16
Velikost	50
Max. vhodni tlak [bar]	63.0
Max. temperaturno območje [°C]	70.5
A [mm]	127.0
C [mm]	14000
B [mm]	
Pretok [l/min]	