

Datum: 27.05.2024

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)



## krogelni ventil fina nastavitvev, nikljana lahka medenina, G 2

Kategorija: [Potable water ball valves with fine adjustment](#)  
Šifra: **103405RIE**

(slika je simbolična)

### Kratek opis

Ball valve fine adjustment, Potable water suitable, nickel-plated bright brass, Temp. -15 °C to 100 °C, G 2, PN max 40 bar

Brass ball valves in the standard series with fine adjustment.

Unlike our classic standard ball valves (open-close function), this model features a special stem technology that allows finely modulated opening and closing of the line.

The flow rate can be regulated extremely precisely as a result.

The cock is made of low-lead brass with a bare brass surface on the inside. It is thus safe to use with drinking water. This valve complies with the European standard EN 13828 and the working paper DVGW W 570.

### Tehnične Specifikacije

|                               |                                                                         |
|-------------------------------|-------------------------------------------------------------------------|
| Min. delovna temperatura [°C] | -15                                                                     |
| DVGW odobritev                | DIN EN 13828:2003-12, DVGW W 570                                        |
| Kolo                          | Plastic                                                                 |
| Krogelno tesnilo              | PTFE                                                                    |
| Krogla                        | Chrome-plated brass                                                     |
| Material navojev              | Brass with a bare metal surface                                         |
| Navoj                         | G 2                                                                     |
| Ohišje                        | Nickel-plated brass (outside), brass with a bare metal surface (inside) |
| Standardni navoj              | G thread acc. to DIN EN ISO 228-1                                       |
| Stebelno tesnilo              | NBR                                                                     |
| Max. obratovalni tlak [bar]   | 40                                                                      |
| DN                            | 50                                                                      |
| Max. delovna temperatura [°C] | 100                                                                     |
| L [mm]                        | 110.2                                                                   |
| B [mm]                        | 123.0                                                                   |
| A [mm]                        | 130.0                                                                   |