



(slika je simbolična)

krogelni ventil nerjavno jeklo, Pneumat. vklop, Rp 2 1/2

Kategorija: [Stainless steel ball valve, double-acting actuator](#)
Šifra: **103603RIE**

Kratek opis

2-way stainless steel ball valve, Pneumat. actuation drive, double-acting, Operating temp. -20°C to 70°C, Rp 2 1/2, PN max 63 bar
2-way cock, 3-piece, full bore.
Pneumatic actuators, double- or single acting version and integrated end-position feedback.
Standardised interfaces:
Actuator/valve interface: Four or eight female threads in the actuator housing acc. to EN ISO 5211.
Actuator/control valve interface: Acc. to NAMUR or VDI/VDE 3845.
Actuator/signalling device interface: Acc. to VDI/VDE 3845 (NAMUR).

Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Adapter ventila	Acc. to NAMUR Stainless steel
Material krogelnega ventila	1.4401, with ISO flange plate Rp 2 1/2
Navoj	Anodised aluminium
Pogonski material	PTFE
Premaz za krogelni ventil	NBR
Premaz za pogon	double-acting
Različica	5.5
Priporočeni vodeni tlak [bar]	10
Max. vodeni tlak aktuatorja [bar]	60.0
D [mm]	63
Max. obratovalni tlak [bar]	65
DN	70
Max. delovna temperatura [°C]	89
a/f [mm]	90
Kot vrtenja [°]	180.0
A [mm]	185.0
L [mm]	238.0
B [mm]	