



(slika je simbolična)

## krogelni ventil nerjavno jeklo, pnevmatski vklop, Rp 1/2

Kategorija: [Stainless steel ball valve, single-acting actuator](#)  
Šifra: **103589RIE**

### Kratek opis

Stainless steel ball valve, Pneumatic actuation drive, single-acting, Operating temp. -20 °C to 150 °C, Rp 1/2, PN max. 160 bar

Ball valves with pneumatic actuator. Pneumatic, double-piston, part-turn actuator, double-rocker principle.

### Tehnične Specifikacije

|                                |                                                              |
|--------------------------------|--------------------------------------------------------------|
| Min. delovna temperatura [°C]  | -20                                                          |
| Min. temperaturno območje [°C] | -20                                                          |
| Adapter ventila                | Supplied as standard                                         |
| Material krogelnega ventila    | Stainless steel 1.4401/1.4301/1.4310/1.4408, with ISO flange |
| Navoj                          | Rp 1/2                                                       |
| Pogonski material              | Anodised aluminium                                           |
| Premaz za krogelni ventil      | PTFE / FKM                                                   |
| Premaz za pogon                | NBR                                                          |
| Različica                      | single-acting - spring to close                              |
| Max. vodeni tlak [bar]         | 5.6                                                          |
| DN                             | 15                                                           |
| L [mm]                         | 61.0                                                         |
| Max. temperaturno območje [°C] | 80                                                           |
| Kot vrtenja [°]                | 90                                                           |
| B [mm]                         | 147.0                                                        |
| Max. delovna temperatura [°C]  | 150                                                          |
| PN [bar]                       | 160                                                          |
| A [mm]                         | 221.0                                                        |