

krogelni ventil nerjavno jeklo, pnevmatski vklop, Rp 3/4



Kategorija: [Stainless steel ball valve, double-acting actuator](#)
Šifra: **158755RIE**

(slika je simbolična)

Kratek opis

Stainless steel ball valve, Pneumatic actuation drive, double-acting, Operating temp. -20 °C to 150 °C, Rp 3/4, PN max. 100 bar
Ball valves with pneumatic actuator. Pneumatic, double-piston, part-turn actuator, double-rocker principle.

Tehnične Specifikacije

Min. delovna temperatura aktuatorja [°C]	-20
Min. delovni tlak krogelnega ventila [°C]	-20
Adapter ventila	Integrated to NAMUR
Material	Stainless steel
krogelnega ventila	1.4401/1.4301/1.4310/1.4408, with ISO flange
Navoj	Rp 3/4
Pogonski material	Anodised aluminium
Premaz za krogelni ventil	PTFE / FKM
Premaz za pogon	NBR
Različica	double-acting
Priporočeni vodeni tlak [bar]	5.6
Max. vodeni tlak aktuatorja [bar]	8.4
DN	20
L [mm]	70.0
Max. delovna temperatura aktuatorja [°C]	80
Kot vrtenja [°]	90
PN [bar]	100
Max. delovni tlak krogelnega ventila [°C]	150
B [mm]	160.5
A [mm]	174.2