

Datum: 27.05.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



(slika je simbolična)

krogelni ventil nerjavno jeklo, za DIN 3202-M3, G 3/4

Kategorija: [Ball valves 2-piece, length acc. to DIN 3202-M3](#)
Šifra: **135354RIE**

Kratek opis

Stainless steel ball valve, 2-piece, length acc. to DIN 3202-M3, G 3/4, DN 20, Operating temp. -20 °C to 180 °C, PN max. 63 bar

Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Bore diameter padlock	ca. 7.5 mm
Delovni tlak	max. 63 bar (dependent on temperature)
Krogelno tesnilo	PTFE (15 % glass fibre reinforced)
Krogla	Stainless steel 1.4401
Navoj	G 3/4
Ohišje	Stainless steel 1.4408
Ročica	Stainless steel 1.4301, with plastic coating
Standardni navoj	G thread acc. to DIN EN ISO 228-1
Stebelno tesnilo	PTFE
DN	20
B [mm]	59.0
L [mm]	80.0
A [mm]	105.0
Max. delovna temperatura [°C]	180