

Datum: 27.05.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



(slika je simbolična)

krogelni ventil s prirobnico, Pneumat. vklop, DN 15

Kategorija: [Stainless steel ball valves compact flange type](#)
Šifra: **103638RIE**

Kratek opis

Compact flange ball valve, Pneumat. actuation drive, double-acting, Stainless steel, Operating temp. -10°C to 200°C, PN max 40 bar
2-way ball valves compact flange type, full bore.
Pneumatic actuators, double- or single acting version and integrated end-position feedback.

Tehnične Specifikacije

Delovna temperatura	-10 °C to 200 °C (depending on the operating pressure)
Adapter ventila	Acc. to NAMUR
Material krogelnega ventila	Stainless steel 1.4408, with ISO flange
Pogonski material	Anodised aluminium
Premaz za krogelni ventil	PTFE
Premaz za pogon	NBR
Različica	double-acting
Max. vodeni tlak [bar]	5.5
DN	15
C [mm]	40.0
PN [bar]	40
E [mm]	45.0
F [mm]	61.5
Kot vrtenja [°]	90
D [mm]	95.0
A [mm]	116.0
B [mm]	125.0