

Datum: 27.05.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



(slika je simbolična)

krogelni ventil, visoki tlak, G notranji navoj, jeklo, G 1

Kategorija: [High-pressure ball valve, steel, G female thread](#)
Šifra: **103520RIE**

Kratek opis

Ball valve, High pressure design, G interior thread, Steel,
Operating temperature -10 °C to 100 °C, G 1, DN 25, PN
max. 420 bar
For liquid and lubricating media.
Available versions:
- For solderless tube fittings acc. to DIN 2353, lightweight
series acc. to ISO 8434-1.
- For solderless tube fittings acc. to DIN 2353, heavy-duty
series acc. to ISO 8434-1.
- With female pipe thread acc. to DIN ISO 228-1 (BSP).

Tehnične Specifikacije

Min. delovna temperatura [°C]	-10
Bore inball	Full bore
Gred izbirnika	Steel
Kontrolno kroglično tesnilo	POM
Krogla	Hard-chrome plated steel
Navoj	G 1
Ohišje	Steel
Tesnilo gredi izbirnika	NBR
DN	25
Max. delovna temperatura [°C]	100
L [mm]	115.0
B [mm]	128.0
A [mm]	187.0
Max. obratovalni tlak [bar]	420