

Datum: 27.05.2024

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)



(slika je simbolična)

## L-obročni del, na votli vijak G 3/8, zun. Ø 10 mm

Kategorija: [L-ring nipple](#)  
Šifra: **108841RIE**

### Kratek opis

L-ring piece, for hollow screw G 3/8, for hose exterior Ø 10,  
Working pressure -0.98 to 16 bar, Operating temp. -20 °C to  
70 °C

The advanced version of our highly successful push-in  
fittings series manufactured in nickel-plated brass.

Advantages of this new, optimised series:

- Much easier connection and disconnection of the hose,  
even with repeated mounting
- Can also be used for non-calibrated hoses
- Suitable for vacuum operation

### Tehnične Specifikacije

|                                  |                              |
|----------------------------------|------------------------------|
| Min. delovna temperatura<br>[°C] | -20                          |
| Min. delovni tlak [bar]          | -0.98                        |
| Material                         | Nickel-plated brass          |
| Priporočena cev                  | PA, PU                       |
| Rokav                            | Black nickel-plated<br>brass |
| Serijska                         | click-clock                  |
| Vpenjalni obroč                  | Stainless steel              |
| Za banjo vijak                   | G 3/8                        |
| Za cevi O.D. [mm]                | 10                           |
| Max. delovni tlak [bar]          | 16                           |
| L2 [mm]                          | 20.0                         |
| L1 [mm]                          | 28.0                         |
| Max. delovna temperatura<br>[°C] | 70                           |