



(slika je simbolična)

MikroFilter »variobloc«Kov. pos.0.01 µmVel. 2G 3/4

Kategorija: [Microfilter with metal bowl, incl. sight glass](#)
Šifra: **125323RIE**

Kratek opis

Microfilter »variobloc«, Metal container incl. viewing tube, 0.01 µm, Size 2, G 3/4, Input pressure max. 20 bar, Temp. max. 50 °C
Borosilicate filter for all applications where compliance with strict compressed air purity requirements is vital.
As the second stage downstream of the standard filter, the micro-filter removes 99.999 % of even the finest remaining particles from water, oil and dirt with practically zero residues (filter rating: 0.01 µm).

Tehnične Specifikacije

Kakovost zraka po ISO	Class 1 dirt, class 1 oil
8573.1	At $P_1 = 7$ bar and pressure drop $\Delta p = 0,1$ bar
Merjenje pretoka	G 3/4
Navoj	Metal container with viewing tube
Posoda	variobloc
Serija	0.01
Rang filtra [µm]	2
Velikost	20
Max. vhodni tlak [bar]	26.0
C [mm]	Max. temperatura medija [°C]
Max. temperatura medija [°C]	50
A [mm]	70.0
Max. sobna temperatura [°C]	80
Učinkovitost [%]	99.999
B [mm]	202.0
Pretok [l/min]	1100