

Datum: 27.05.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



(slika je simbolična)

MikroFilter z diferencialnim manometrom, 0.01 µm, G 1 1/4

Kategorija: [Microfilter with differential pressure gauge](#)
Šifra: **101565RIE**

Kratek opis

Microfilter with differential pressure gauge, 0.01 µm, G 1 1/4, Input pressure 4 - 12 bar, Medium / ambient temp. 5 °C to 60 °C
Ideal for filtering out aerosols and solid impurities larger than 0.01 µm.
Micro-filters should always be used in conjunction with a pre-filter.

Tehnične Specifikacije

Element filtra	Borosilicate (with glass-fibre material and foam plastic) At $P_1 = 6$ bar and pressure drop $\Delta_p = 1.5\%$
Merjenje pretoka	G 1 1/4
Navoj	Aluminium
Ohišje	Aluminium
Posoda filtra	Aluminium
Rang filtra [µm]	0.01
Max. označeni razpon diferencialnega manometra [bar]	2
Min. vhodni tlak [bar]	4
Min. sobna temperatura [°C]	5
Min. temperatura medija [°C]	5
Max. vhodni tlak [bar]	12
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
C [mm]	72.0
Učinkovitost [%]	99.9999
A [mm]	118.0
B2 [mm]	520.0
B1 [mm]	617.5
D [mm]	658.0
Pretok [l/min]	4580