



(slika je simbolična)

MikroFilter z diferencialnim manometrom, 0.01 µm, G 2

Kategorija: [Microfilter with differential pressure gauge](#)Šifra: **101567RIE**

Kratek opis

Microfilter with differential pressure gauge, 0.01 µm, G 2,
Input pressure 4 - 12 bar, Medium / ambient temperature 5
°C to 60 °C

Ideal for filtering out aerosols and solid impurities larger
than 0.01 µm.

Micro-filters should always be used in conjunction with a
pre-filter.

Tehnične Specifikacije

Element filtra	Borosilicate (with glass-fibre material and foam plastic) At $P_1 = 6$ bar and pressure drop $\Delta_p =$ 1.5%
Merjenje pretoka	G 2
Navoj	Aluminium
Ohišje	Aluminium
Posoda filtra	Aluminium
Rang filtra [µm]	0.01
D [mm]	1.238.0
Max. označeni razpon diferencialnega manometra [bar]	2
Min. vhodni tlak [bar]	4
Min. sobna temperatura [°C]	5
Min. temperatura medija [°C]	5
Max. vhodni tlak [bar]	12
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
C [mm]	72.0
Učinkovitost [%]	99.9999
A [mm]	118.0
B2 [mm]	810.0
B1 [mm]	907.5
Pretok [l/min]	9000