

Datum: 27.05.2024

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)



(slika je simbolična)

## MikroFilter za visoke pritiske do 60 bar, 0.01 µm, G 1

Kategorija: [Microfilters for high pressures up to 60 bar](#)  
Šifra: **101183RIE**

### Kratek opis

Microfilter for high pressures up to 60 bar, manual bleeder valve, 0.01 µm, G 1, Brass container, Operating temp. 0 °C to 90 °C

Fine filter for all applications with particularly strict compressed air purity requirements. Micro-filters should always be used in conjunction with a standard filter connected upstream to trap coarse impurities and protect the micro-filter inserts.

### Tehnične Specifikacije

|                               |                                                         |
|-------------------------------|---------------------------------------------------------|
| Element filtra                | Borosilicate                                            |
| Merjenje pretoka              | At $P_2 = 6$ bar and pressure drop $\Delta_p = 0.5$ bar |
| Navoj                         | G 1                                                     |
| Ohišje                        | Aluminium                                               |
| Posoda                        | Brass                                                   |
| Tesnilo                       | NBR                                                     |
| Rang filtra [µm]              | 0.01                                                    |
| C [mm]                        | 29.0                                                    |
| Max. vhodni tlak [bar]        | 60                                                      |
| A [mm]                        | 80.0                                                    |
| Max. delovna temperatura [°C] | 90                                                      |
| Učinkovitost [%]              | 99.9999                                                 |
| B [mm]                        | 196.0                                                   |
| Pretok [l/min]                | 2300                                                    |