

Plastic.

For blowing out and cleaning machines, engines, bearings, sliding surfaces, bores of all kinds, hollow parts, moulds, etc.

The compressed air guns are supplied in a blister package with Euro holes.

| | |
|-------------------------|-----------------|
| Material | Plastic |
| Operating pressure max. | 10 bar |
| Operating temperature | -20 °C to 45 °C |

Blow gun with short nozzle

| Art. No. | Type No. | Type of connection |
|----------|----------|---|
| 125657 | 50 D | G 1/4 IT |
| 125364 | 50 F | Push-in plug for DN 7.2 - 7.8 couplings |

Blow gun with extension tube

| Art. No. | Type No. | Type of connection |
|----------|----------|---|
| 125658 | 51 D | G 1/4 IT |
| 125365 | 51 F | Push-in plug for DN 7.2 - 7.8 couplings |

Blow gun with extension tube 105 mm and collet cover

| Art. No. | Type No. | Type of connection |
|----------|----------|---|
| 125503 | 52 D | G 1/4 IT |
| 125366 | 52 F | Push-in plug for DN 7.2 - 7.8 couplings |

Blow gun with extension tube 105 mm and noise-reducing nozzle

| Art. No. | Type No. | Type of connection |
|----------|----------|---|
| 125504 | 53 D | G 1/4 IT |
| 125367 | 53 F | Push-in plug for DN 7.2 - 7.8 couplings |



50 D



51 D



52 D



53 D