

Datum: 28.05.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



(slika je simbolična)

Naoljevalnik »Stinard«PC zbir.Zašč. kletkaVel. 4G 1 1/4

Kategorija: [Oil-mist lubricator with PC bowl and bowl guard](#)
Šifra: **101028RIE**

Kratek opis

Mist oiler »Standard«, PC container, protective cage, Size 4, G 1 1/4, Input pressure max. 16 bar, Medium/ambient temp. max. 60 °C
Proportional lubricators, oil can be filled under pressure.

Tehnične Specifikacije

Merjenje pretoka	At $P_2 = 6$ bar and pressure drop $\Delta p = 1$ bar
Navoj	G 1 1/4
Ohišje	Die-cast zinc, painted silver
Posoda	Polycarbonate container with protective cage
Razred olja	CL 32 acc. to DIN 51517-ISO VG 32
Serijska	Standard
Tesnilo	NBR
Vidna kupola	PA
Velikost	4
Max. vhodni tlak [bar]	16
DN	40
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
C [mm]	70.0
A [mm]	137.0
D [mm]	232.0
Pretok [l/min]	9000