

Datum: 26.05.2024

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)



## Naoljevalnik »variobloc« PC zbir. Protec. cage Vel. 2G 1

Kategorija: [Oil-mist lubricator with PC bowl and bowl guard](#)  
Šifra: **124820RIE**

(slika je simbolična)

### Kratek opis

Mist oiler »variobloc«, PC container, protective cage, Size 2, G 1, Input pressure max. 16 bar, Medium / ambient temp. max. 50°C

Proportional lubricators, oil can be filled under pressure.

Approved series in modern industrial design, with the following key benefits:

- Simple handling
- Convenient modular assembly thanks to innovative fasteners
- Excellent flow values

### Tehnične Specifikacije

|                              |                                                       |
|------------------------------|-------------------------------------------------------|
| Merjenje pretoka             | At $P_1 = 6$ bar and pressure drop $\Delta p = 1$ bar |
| Navoj                        | G 1                                                   |
| Ohišje                       | Die-cast zinc                                         |
| Posoda                       | Polycarbonate container with protective cage          |
| Razred olja                  | CL 32 acc. to DIN 51517-ISO VG 32                     |
| Serija                       | variobloc                                             |
| Tesnilo                      | NBR                                                   |
| Vidna kupola                 | PA                                                    |
| Velikost                     | 2                                                     |
| Max. vhodni tlak [bar]       | 16                                                    |
| Max. sobna temperatura [°C]  | 50                                                    |
| Max. temperatura medija [°C] | 50                                                    |
| C [mm]                       | 57.0                                                  |
| A [mm]                       | 124.0                                                 |
| B [mm]                       | 224.0                                                 |
| Pretok [l/min]               | 7500                                                  |