



## **Natančen tlačni regulator »FUTURA«, Velikost 2, G 3/8, 0.5-16 bar**

Kategorija: [Precision pressure regulators](#)  
Šifra: **139482RIE**

(slika je simbolična)

### **Kratek opis**

Precision pressure regulator »FUTURA«, incl. pressure gauge, Size 2, G 3/8, Input pressure max. 16 bar, Control range 0.5 - 16 bar  
Precision diaphragm pressure regulators with self-relieving design and excellent flow rates in modern design for applications requiring an extremely accurate working pressure.  
The regulator button can be latched and locked.

### **Tehnične Specifikacije**

|                                |                                                                         |
|--------------------------------|-------------------------------------------------------------------------|
| Min. temperaturno območje [°C] | -10                                                                     |
| Membrane                       | NBR                                                                     |
| Merjenje pretoka               | At $P_1 = 10$ bar, $P_2 = 6.3$ bar and pressure drop $\Delta p = 1$ bar |
| Navoj                          | G 3/8                                                                   |
| Ohišje                         | PA66 GF60                                                               |
| Poraba zraka                   | Yes                                                                     |
| Priključni navoj               | Material: Die-cast zinc                                                 |
| Serijska                       | FUTURA                                                                  |
| Srednje                        | Compressed air, neutral gases                                           |
| Tesnilo                        | NBR                                                                     |
| Min. krmilno območje [bar]     | 0.5                                                                     |
| Velikost                       | 2                                                                       |
| Max. notranja poraba zraka     | 2.6 l/min (depending on secondary pressure)                             |
| Max. krmilno območje [bar]     | 16                                                                      |
| Max. vhodni tlak [bar]         | 16                                                                      |
| Zaslon manometra max. [bar]    | 25                                                                      |
| Max. temperaturno območje [°C] | 50                                                                      |
| A [mm]                         | 63.0                                                                    |
| C [mm]                         | 110.0                                                                   |
| B [mm]                         | 150.0                                                                   |
| Pretok [l/min]                 | 4500                                                                    |