



(slika je simbolična)

## Navojni vtični priključek, G 1/8 o. vtični prikllop Ø 4 mm

Kategorija: [Push-in plug, parallel male thread with O-ring](#)  
Šifra: **135293RIE**

### Kratek opis

Thread plug nipple, G 1/8 o. , Plug connenction Ø 4 mm,  
Stainless steel 1.4404

For use in more aggressive environments and corrosive media.

Only recommended for use in combination with stainless steel quick connectors type 844 ff. Suitability testing for use with other series is the responsibility of the user.

### Tehnične Specifikacije

|                               |                           |
|-------------------------------|---------------------------|
| Min. delovna temperatura [°C] | -20                       |
| Min. temperatura medija [°C]  | -20                       |
| Min. delovni tlak [bar]       | -0.98                     |
| Material                      | Stainless steel<br>1.4404 |
| Navoj                         | G 1/8                     |
| Primerni materiali za cevi    | PVDF, PTFE, PA, PU        |
| Standardni navoj              | DIN EN ISO 228-1          |
| Tesnilo                       | FPM                       |
| Priključek [mm]               | 4                         |
| a/f [mm]                      | 14                        |
| Max. delovni tlak [bar]       | 20                        |
| L1 [mm]                       | 34.8                      |
| Max. delovna temperatura [°C] | 150                       |
| Max. temperatura medija [°C]  | 150                       |