



(slika je simbolična)

Okrogli cilinder, enosmerni, bat Ø 25, hod 50, G 1/8

Kategorija: [Metalwork](#)
Šifra: **105839RIE**

Kratek opis

Round cylinder, ISO 6432, single-acting, Magnet, Piston Ø 25, Stroke 50, G 1/8, Working pressure max. 10 bar, Temp. -10°C to 80°C
Single and double-acting cylinders, with magnetic piston.
Suitable for filtered, unlubricated or lubricated compressed air.
If lubrication is used, it must be continuous.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Bat	Synthetic (acetal) resin
Batnica	C45 steel, hard chrome-plated
Cushioning	non-cushioned
Ffunkcija	single-acting
Gewinde Kolbenstange	male piston rod
Magnet	with magnet
Navoj na batnici	M10x1.25
Oblika	Flanged joint between stainless steel barrel and heads
Ovoj	Stainless steel 1.4301
Povezava	G 1/8
Standard	acc. to ISO 6432
Starting position	pressureless in the retracted position
Tesnilo	NBR
Min. nastavljeni tlak [bar]	0.6
Max. delovni tlak [bar]	10
Bat Ø [mm]	25
Stroke [mm]	50
Max. temperaturno območje [°C]	80