



(slika je simbolična)

Okrogli cilinder »MI«delujoč v dveh smerehbatØ 32hod 600G 1/8

Kategorija: [Round cylinder, double-acting, with magnet, CM](#)
Šifra: **114903RIE**

Kratek opis

Round cylinder »MI«, double-acting, Magnet, Piston Ø 32, Stroke 600, G 1/8, Working pressure 1 - 10 bar, Temp. -20 °C to 70 °C

These round cylinders are available in the following versions:

- »MI« Series, double-acting, Ø 8 to 25 acc. to ISO 6432
- »MI« Series, double-acting, Ø 32 to 40
- »MSI« Series, single-acting, pressureless in the retracted position, Ø 32 to 40

Suitable for filtered, unlubricated or lubricated compressed air.

If lubrication is used, it must be continuous.

»CA« type = bottom cover with male thread - hinge model
»CM« type = bottom cover with male thread, round - hinge model

Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Bat	Aluminium
Batnica	Stainless steel 1.4301
Cushioning	non-cushioned
ET batnice	M10x1.25
Ffunkcija	double-acting
Gewinde Kolbenstange	male piston rod
Magnet	with magnet
Ovoj	Stainless steel 1.4301
Povezava	G 1/8
Serija	MI series
Tesnilo	NBR
Vrsta	CM type
Min. delovni tlak [bar]	1
Max. delovni tlak [bar]	10
Batnica Ø [mm]	12
Bat Ø [mm]	32
Max. temperaturno območje [°C]	70
Stroke [mm]	600