

Datum: 23.05.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



(slika je simbolična)

Pnevmatski izpustni kontrolni ventil -z navojem, G 1/8 8

Kategorija: [Metalwork](#)
Šifra: **106827RIE**

Kratek opis

Pneumatically releasable check valve »lineonline«, Hose - thread, G 1/8, for hose Ø 8 mm, Operating pressure max. 10 bar

For stopping and positioning the cylinder. If a signal is present at the pilot port, air can flow to and from the cylinder. If no pilot signal is present, the cylinder exhaust port is shut off by the stop valve. The cylinder is stopped.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Navoj	G 1/8
Notranji deli	Nickel-plated brass, brass, technopolymer, stainless steel
Pnevmatski simboli	On housing
Telo	Technopolymer
Tesnilo	NBR
Nadzor zraka	4 mm
Za cevi Ø [mm]	8
Max. obratovalni tlak [bar]	10
I [mm]	18.7
B [mm]	49.7
Max. temperaturno območje [°C]	60
A [mm]	66.2
Pretok pri 6,3 bar in Δp 1,0 bar [l/min]	790