

Datum: 27.05.2024

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)



(slika je simbolična)

## Pnevmatski zapotni ventil, G 1/2, G 1/2 i., G 1/8

Kategorija: [Pneumatically piloted stop valves](#)  
Šifra: **107060RIE**

### Kratek opis

Pneumatically piloted stop valve, G 1/2, G 1/2 i., G 1/8,  
Working pressure 0.3-10 bar, Temperature -10°C to 60°C  
For stopping and positioning the cylinder movement:  
If a control signal is present at port 3 (see drawing), air can  
flow to and from the cylinder. If no control signal is present,  
the cylinder exhaust air is shut off by the unidirectional  
valve. The cylinder is stopped. Releasable unidirectional  
valves are screwed directly onto the cylinder instead of the  
normal pipe connections.  
Note: Pilot pressure is depending on operating pressure.

### Tehnične Specifikacije

|                                 |                                                                |
|---------------------------------|----------------------------------------------------------------|
| Min. sobna temperatura [°C]     | -10                                                            |
| Min. temperatura medija [°C]    | -10                                                            |
| Material                        | Nickel-plated brass                                            |
| Port 1                          | G 1/2                                                          |
| Port 2                          | G 1/2                                                          |
| Port 3                          | G 1/8                                                          |
| Tesnilo                         | NBR                                                            |
| Vgradni položaj                 | Any, ring piece must<br>be pos. before<br>tightening the valve |
| Min. obratovalni tlak [bar]     | 0.3                                                            |
| Min. vodeni tlak [bar]          | 0.5                                                            |
| Max. vodeni tlak [bar]          | 2.5                                                            |
| Max. obratovalni tlak [bar]     | 10                                                             |
| C [mm]                          | 32.0                                                           |
| B [mm]                          | 52.0                                                           |
| Max. sobna temperatura [°C]     | 60                                                             |
| Max. temperatura medija<br>[°C] | 60                                                             |