

Datum: 23.05.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



polietilen cevi, Ø 3x1.5 mm, naravna , rola 25 m

Kategorija: [Polyethylene hose \(LD-PE\)](#)
Šifra: **113590RIE**

(slika je simbolična)

Kratek opis

Polyethylene hose (LD-PE), Temperature -10 °C to 60 °C,
Hose Ø 3x1.5 mm, PN at 20 °C max. 21 bar, natural (milky),
Roll of 25 m

Low-priced, calibrated hose for use with screw fittings.
With its soft and flexible character, combined with relatively
high strengths and good resistance to stress cracking, this
hose is ideal for use in the following types of application:

- Flexible pneumatic lines in the low-pressure range,
providing no special resistance to greases, oils or other
hydrocarbons is required.
- Compressed air control lines.
- Vacuum lines (suitable for vacuum up to 10 x 8 mm).
- Supply lines of all kinds.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Barva	natural
Material	Polyethylene (LD- PE)
I.D. cevi [mm]	1.5
O.D. cevi [mm]	3
Max. obratovalni tlak pri 20 ° C [bar]	21
Dolžina koluta [m]	25
Max. temperaturno območje [°C]	60