

Datum: 23.05.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



(slika je simbolična)

Pretočni ventil, ET zgoraj, aluminij, krogelni ventil

Kategorija: [Check valve, male thread at top](#)
Šifra: **108424RIE**

Kratek opis

Flow valve, ET top, Required suction capacity $p_u = 0.3$ bar
1.2 l/min, $p_u = -0.6$ bar l/min 1.3, Aluminium, Ball seat valve
Check valves close the vacuum line if the suction pad is not covered, thus maintaining the vacuum. The valves are protected against dirt by a replaceable sieve. This valve series is suitable for all suction pads in our standard range.

Tehnične Specifikacije

Navoj 1	M5 ET
Navoj 2	M5 IT
Ohišje	Aluminium
Vrsta gradnje	Ball seat valve (ball in brass seat)
Zahtevana stopnja evakuacije za $p_u = -0.3$ bar [l/min]	1.2
Zahtevana stopnja evakuacije za $p_u = -0.6$ bar [l/min]	1.3
Teža [g]	2.2
Dolžina [mm]	15.5
Max. Izpušna pretočna hitrost [l/min]	80