

Datum: 27.05.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



Ravni pot.i fitting G 1/2 , zun. premera 14 mm

Kategorija: [Male connector, parallel male thread, outer hex](#)
Šifra: **135073RIE**

(slika je simbolična)

Kratek opis

Straight push-in fitting, Exterior hexagonal, G 1/2 o. for hose exterior Ø 14 mm, Working pressure -0.98 - 20 bar, 1.4404
For use in more aggressive environments and corrosive media.
The suitability test for the individual application is the user's responsibility.

Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Min. delovni tlak [bar]	-0.98
Material	Stainless steel
	1.4404
Navoj	G 1/2
Primerni materiali za cevi	PVDF, PTFE, PA, PU
Standardni navoj	DIN EN ISO 228-1
Tesnilo	FPM
Za cevi O.D. [mm]	14
Max. delovni tlak [bar]	20
a/f [mm]	27
L1 [mm]	30.0
Max. delovna temperatura [°C]	150
Max. temperatura medija [°C]	150