

Datum: 27.05.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



Ravni priključek POM, za cev zunanja Ø 4 mm

Kategorija: [Unions - POM](#)
Šifra: **110278RIE**

(slika je simbolična)

Kratek opis

Straight connector POM, for hose exterior Ø 4 mm, working pressure -0.95 to 16 bar
Lightweight, push-in fittings distinguished by high strength, toughness, resistance to abrasion and impact resistance - ideal for a wide range of applications.
All our push-in fittings made of POM have the following approvals:
drinking water DVGW, KTW, FDA and NSF.
Plastic and metal tubes are connected together quickly and easily. Suitable for compressed air or liquids, with good resistance to a large number of chemicals.

Tehnične Specifikacije

Min. delovna temperatura v zraku [°C]	-20
Min. delovni tlak [bar]	-0.95
Material	Acetal polymer (POM)
Min. delovna temperatura v vodi [°C]	1
Za cevi O.D. [mm]	4
Max. delovni tlak [bar]	16
L1 [mm]	32.6
Max. delovna temperatura v zraku [°C]	65
Max. delovna temperatura v vodi [°C]	70