



(slika je simbolična)

## Regulator tlaka lineonline, G 1/4 (izhodni), Ø 8 (vhodni)

Kategorija: [Metalwork](#)  
Šifra: **106751RIE**

### Kratek opis

Pressure regulator »lineonline«, thread (outlet) - hose (inlet), G 1/4, for hose Ø 8 mm, Operating pressure 2 - 10 bar  
Particularly suitable for installation between the valve and cylinder and as a pressure regulator in secondary branches of the pneumatic system. The regulator is fitted with a pressure limiting valve for overpressure exhaust.

### Tehnične Specifikacije

|                                |                                                            |
|--------------------------------|------------------------------------------------------------|
| Min. temperaturno območje [°C] | -20                                                        |
| Navoj                          | G 1/4                                                      |
| Notranji deli                  | Nickel-plated brass, brass, technopolymer, stainless steel |
| Pnevmatski simboli             | On housing                                                 |
| Telo                           | Technopolymer                                              |
| Tesnilo                        | NBR                                                        |
| Min. krmilno območje [bar]     | 1                                                          |
| Min. obratovalni tlak [bar]    | 2                                                          |
| Max. krmilno območje [bar]     | 8                                                          |
| Za cevi Ø [mm]                 | 8                                                          |
| Max. obratovalni tlak [bar]    | 10                                                         |
| I [mm]                         | 18.7                                                       |
| B [mm]                         | 58.0                                                       |
| Max. temperaturno območje [°C] | 60                                                         |
| A [mm]                         | 70.6                                                       |
| Pretok pri 6,3 bara [NI/min]   | 600                                                        |