



(slika je simbolična)

Serv. enota 3-delna »variobloc« Zašč. kletka Vel. 2G 3/4

Kategorija: [Service unit, 3-piece with PC bowl and bowl guard](#)
Šifra: **124860RIE**

Kratek opis

Service unit 3-part »variobloc«, PC container and protective cage, Size 2, G 3/4, Input pressure max. 16 bar, Temp. max. 50 °C

Three-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator. Approved series in modern industrial design, with the following key benefits:

- Simple handling
- Convenient modular assembly thanks to innovative fasteners
- Excellent flow values

Tehnične Specifikacije

Membrane	NBR
Merjenje pretoka	At $P_1 = 10$ bar, $P_2 = 6$ bar and pressure drop $\Delta p = 1$ bar
Navoj	G 3/4
Odtok kondenzata	Manual
Ohišje	Die-cast zinc
Posoda	Polycarbonate container with protective cage variobloc
Serija	NBR
Tesnilo	PA
Vidna kupola	POM
Vzmet pokrova motorja	0.5
Min. krmilno območje [bar]	2
Velikost	10
Max. krmilno območje [bar]	10
Zaslon manometra max. [bar]	16
Max. vhodni tlak [bar]	40
Rang filtra [μm]	50
Max. sobna temperatura [°C]	50
Max. temperatura medija [°C]	98.0
C [mm]	210.0
A [mm]	274.0
B [mm]	5000
Pretok [l/min]	