



(slika je simbolična)

Servisna enota 2-delna »multifix-mali«, Kovinska posoda, G 1/8

Kategorija: [Service unit, 2-piece with metal bowl](#)

Šifra: **100396RIE**

Kratek opis

Service unit 2-part »multifix-mini« with metal container, Size 0, G 1/8, Input pressure max. 12 bar, Control range 0.5 - 10 bar

Two-piece service units consisting of a diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator.

Tehnične Specifikacije

Merjenje pretoka	At $P_1 = 10$ bar, $P_2 = 6.3$ bar and pressure drop $\Delta p = 1$ bar
Navoj	G 1/8
Odtok kondenzata	Semi-automatic
Ohišje	Die-cast zinc
Posoda	Metal container
Serijska	multifix-mini
Tesnilo	NBR
Vidna kupola	Zinc-glass-NBR
Vzmet pokrova motorja	POM-brass
Min. krmilno območje [bar]	0.5
DN	5
Rang filtra [μ m]	5
Max. krmilno območje [bar]	10
Max. vhodni tlak [bar]	12
Zaslon manometra max. [bar]	16
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
C [mm]	63.0
A [mm]	80.0
D [mm]	99.0
B [mm]	162.0
Pretok [l/min]	700