



(slika je simbolična)

## Servisna enota 2-delna »Stinard« z PC zbiralnik, Velikost 4, G 1

Kategorija: [Service unit, 2-piece with polycarbonate bowl](#)  
Šifra: **174099RIE**

### Kratek opis

Service unit 2-part »Standard« with polycarbonate container, Size 4, G 1, PE max. 16 bar, Control range 0.5 - 10 bar, pilot contr.

Two-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator.

### Tehnične Specifikacije

|                              |                                                                      |
|------------------------------|----------------------------------------------------------------------|
| Merjenje pretoka             | At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar |
| Navoj                        | G 1                                                                  |
| Odtok kondenzata             | Semi-automatic                                                       |
| Ohišje                       | Die-cast zinc / aluminium, painted silver                            |
| Posoda                       | Polycarbonate container                                              |
| Serijska                     | Standard                                                             |
| Tesnilo                      | NBR                                                                  |
| Vidna kupola                 | PA                                                                   |
| Min. krmilno območje [bar]   | 0.5                                                                  |
| Velikost                     | 4                                                                    |
| Max. krmilno območje [bar]   | 10                                                                   |
| Max. vhodni tlak [bar]       | 16                                                                   |
| Zaslona manometra max. [bar] | 16                                                                   |
| DN                           | 25                                                                   |
| Rang filtra [ $\mu$ m]       | 40                                                                   |
| Max. sobna temperatura [°C]  | 60                                                                   |
| Max. temperatura medija [°C] | 60                                                                   |
| Manometer $\varnothing$ [mm] | 63                                                                   |
| C [mm]                       | 129.0                                                                |
| A [mm]                       | 222.0                                                                |
| B [mm]                       | 392.0                                                                |
| Pretok [l/min]               | 4000                                                                 |